

Address

Occupancy Class

TIERED PERFORMANCE COMPLIANCE

Section 9.36 of the National Building Code of Canada

This form is intended to clarify the compliance with Section 9.36, Tier 2 performance path.

Must be completed by a competent person who is knowledgeable, experienced and trained in building design under Section 9.36 of the NBC and acceptable to the Authority Having Jurisdiction.

Conditioned Space Volume	e (m³)			
	e Path 9.36.5. & 9.36.7. n or without secondary suites, buildir floor area does not exceed 20% of			
Input parameters (not required for EnerGuide compliance)		Reference	Model	Proposed Model
Airtightness Level (air exchanges per hour @ 50 Pa)				
Heat Loss/Heat Gain				
HRV efficiency				
Thermal mass (MJ/m²•°C)				
Ventilation rate (I/s)				
Fenestration and door to wall ratio (FDWR) – reference (%)				
Direction of front elevation (clearly circle one)		N NE E S SW W		N NE E SE S SW W NW
Area of windows and doors	Front elevation (m²)			
	Rear elevation (m²)			
	Left elevation (m ²)			
	Right elevation (m²)			
	Total area of windows (m ²)			
	Total area of opaque doors (m²)			
Energy use (GJ)				
Software Information				
Software title		Version		
Is software Hot2000 or ANSI/ASHRAE 140 compliant?				
Modelling summary reports generated for both the reference and proposed			Vaa	L.
houses are required to be attached.			Yes	No

Compliance via Tiered Performance Results (9.36.7.)

Energy Performance Metrics	Reference	Proposed	Target Energy			
(not Required for Energuide Compliance)	Model	Model	Performance			
Total volume of conditioned space within the building or house > 300m³ and where volume is not determined						
Percent heat loss reduction (Required: ≥ 5%) (calculated by subtracting the annual gross space heat loss of the proposed house from the annual gross space heat loss of the reference house and dividing the result by annual gross space heat loss of the reference house)			Achieved:			

Updated January 2024 Page 1 of 2



TIERED PERFORMANCE COMPLIANCE

Section 9.36 of the National Building Code of Canada

Percent improvement (Required: ≥ 10%) (calculated by subtracting the annual energy consumption of the proposed house from the house energy target of the reference house and dividing the result by the house energy target of the				Achieved:		
(calculated by consumption of	e energy target (Required: ≤ 90%) dividing the annual energy of the proposed house by the house of the reference house)			or Achieved:		
	load (≤ reference house)			Yes No		
Total volume of conditioned space within the building or house ≤ 300m³ and where volume is not determined						
Percent house energy target (Required: ≤ 100%) (calculated by dividing the annual energy consumption of the proposed house by the house energy target of the reference house)				Achieved:		
Declaration						
Name		Company				
Email		Phone				
I hereby certify that the design parameters and/or calculations submitted were prepared in full accordance with the operation procedures of the software and:						
Subsection 9.36.7 of the 2020 NBC.						
Alternative Solution (attach supporting documents)						
☐ EnerGuide Rating System, v15. I am a qualified Energy Advisor and the submitted design achieves the minimum 10% annual energy improvement target of 2020 NBC, Tier 2. (a compliance summary will be submitted prior to full occupancy)						
Signature:	<i>E</i>	Pate:				

Where the air-leakage rate is a value less than 3.2 ACH@50 Pa, an airtightness test is required to be conducted. Provide the Airtightness Certificate to buildingdocs@regina.ca once complete but required prior to occupancy.

Updated January 2024 Page 2 of 2